



EPM 333: Economics of Generation & Operation

Power Factor Correction: Problems – 2008/2009

1. Explain why
 - a. Industrial customers usually install capacitors for power factor correction at their premises.
 - b. It is generally not economical to improve the power factor of an installation to unity.
 - c. Installation of capacitors improves voltage regulation.
 - d. Low power factor means higher energy losses.
 - e. Low power factor penalties are charged from industrial customers and not from residential customers.
2. Find the power factor of a station supplying the following loads: 250 kW @ unity PF, 1.5 MW @ 0.9 lagging PF, 700 kW @ 0.9 leading PF, and 1 MW @ 0.8 lagging PF.
3. A single phase 440 V 50 Hz motor operates at a lagging PF of 0.7 and draws a current of 40 A. It is proposed to put a shunt capacitor at the motor terminals to improve the power factor. Find the rating of the capacitor needed to improve the PF to 0.9 lagging.
4. The power factor of a 200 kW, 3-phase, balanced load is to be improved from 0.707 to 0.9 lagging by connecting loss-free capacitors in delta across the 3.3 kV supply. The cost of suitable capacitor and controls is 120 \$/kVAR. The annual tariff charge is 6.50 \$/kVA m.d. and the interest and depreciation charges total 12 %. Calculate:
 - a. The total kVAR rating of the capacitors.
 - b. The required value of capacitance in μF / phase.
 - c. The annual net saving.
 - d. The time taken to save the initial cost of the capacitors and controls.
5. A load of 700 kVA m.d. @ 0.7 PF lagging is to be corrected to the most economical power factor. The annual tariff charge may be taken as 5 \$/kVA m.d. and the initial cost of static, loss-free capacitors, including that of the necessary controls, is 7 \$/kVAR. The annual interest and depreciation charges total 15 %. It is required to calculate:
 - a. The most economical PF.
 - b. The kVAR rating of the capacitor required.
 - c. The annual net saving.
 - d. The time taken to save the initial cost of the capacitors and controls.

6. A customer's supply transformer is rated at 500 kVA and the present load is 350 kW @ 0.7 PF lagging. It is required to add a further load of 110 kW at the same PF. This increase may be achieved by either:
- Installing an additional transformer and its associated switchgear at a total cost of 4 \$/kVA; or
 - Raising the PF of the new total load so that its kVA does not exceed the rating of the existing transformer. The cost of suitable loss-free capacitors is 6 \$/kVAR.
- The interest and depreciation charges for either scheme total 12 % and the annual tariff charge may be taken as 4 \$/kVA m.d. Calculate the total annual running cost of each scheme.

Good Luck

Dr. Mohamed EL-Shimy